

The concrete filler and bonder that will not separate from concrete. Resurfaces chipped and pitted concrete. Resists wear, corrosives, weather, impact. Bonds cracked curbing, masonry, swimming pools. Waterproofs. One application lasts for many years. Low temperature cure (as low as 0°F.)

True-Bond LLT

LOW TEMPERATURE FORMULATION!
FOR USE ON CONCRETE, TILE, METAL OR WOOD!
100% SOLIDS, EPOXY BASED COMPOUND

ACCEPTED BY USDA

Directions

Clean surface of loose aggregates, dirt, grease and oil, and dust. For best results, etch surface with 10 to 15% muriatic acid, flush with clean water, and allow to dry. Pour all of container 'B' into container 'A' and mix thoroughly. Add 3 to 5 parts of dry sand and mix in thoroughly. Brush or trowel on as thick as needed to repair area. Pot life approximately 20 minutes. Because of its high early strength, TRUE-BOND LLT may be opened to traffic in six hours.

Small Quantity Mixing

- 2 cups of Part 'A'
- 1 cup of Part 'B'
- Stir *thoroughly* for 1 minute
- Add 9 cups of dry sand (you may use more or less sand to customize the mix for your application!)
- Mix *thoroughly* again

Coverage: Approximately 200 sq. ft. at approximately 1/4" thickness.

Caution

TRUE-BOND LLT contains an alkaline amine. Avoid contact with skin or eyes. In case of contact, wash skin with soap and water. Flush eyes immediately with water and see doctor. If TRUE-BOND LLT is used indoors, provide adequate ventilation.

EXCLUSIVE
Another quality
product from



R. C. Davis Co. Inc.

Manufacturing Chemists For American Commerce and Industry

the low temperature permanent
concrete patch . . . for holes,
pits and cracks

1600 OLD COUNTRY RD.
PLAINVIEW, N.Y. 11803

FOR ADDITIONAL INFORMATION
AND RE-ORDERS

(516) 694-2080